

MAXIMA QUICK DETACH RINGS - 34MM HIGH (.525") QD RINGS BLACK

Strong, All-Steel With Adjustable Levers; Fit Weaver-Style Bases

Maxima Quick Detach Rings are the most durable and versatile quick detachable mounting system available. Each ring is precision CNC machined from sintered steel technology, a process that allows intricate steel parts to be formed and then fired – retaining the strength properties of steel while adding the necessary ductility that scope mounts require for perfect grip contact around the circumference of the scope. The Maxima QD rings sport the unique Warne indexable lever system which allows the user to remove the optics from the rifle then reattach it without the loss of zero, as well as allowing the location of the lever to be indexed once the rings are affixed to the bases. After the levers are tightened, simply pull out on the lever, turn it to the desired location then let it snap into place. When used on the all steel Warne Maxima bases, we guarantee accuracy of within 1/1000th of an inch when removing and reattaching the optics. Unique to the industry, the Maxima QD has a square stainless steel recoil control key. This ensures a positive recoil engagement surface across the full width and depth of the recoil slot in the base. The recoil control key guarantees the position of the rings will not shift or move under fierce recoil and also protects against peening or swaging when mounted on aluminum bases. Warne Maxima scope rings are designed to fit Warne bases as well as all Weaver cross slot and Mil-Spec Picatinny style bases and rails. Finally, the Maxima QD rings are finished with either a durable DuPont powder coat in matte or gloss black, or electroless nickel finished for a stainless steel look. Warne Maxima rings are then assembled with 4 quality Torx style T-15 socket cap screws.



Attributes

- Name: 34MM HIGH (.525") QD RINGS BLACK
- Manufacturer: WARNE MFG. COMPANY
- Product no.: 947000258
- Mfr. No.: 222LM
- Finish: Matte Blue
- Height: .525"
- Scope Tube Diameter: 34mm
- Size: High
- Style: Weaver-Style Rings
- Delivery weight: 0.227kg
- Shipping height: 23mm
- Shipping width: 112mm
- Shipping length: 157mm
- UPC: 656813102426

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [English: MAXIMA QUICK DETACH RINGS 34MM HIGH \(.525"\) QD RINGS BLACK Safety Instruction Guide](#)
- [Svenska: Säkerhetsinstruktioner för MAXIMA QUICK DETACH RINGS](#)
- [Český: Návod k použití a bezpečnostní pokyny pro MAXIMA QUICK DETACH RINGS](#)

MAXIMA QUICK DETACH RINGS 34MM HIGH (.525") QD RINGS BLACK Safety Instruction Guide

Introduction

Thank you for choosing the Maxima Quick Detach Rings. These rings are designed for durability and versatility in mounting your optics. To ensure safe usage and optimal performance, please read and follow the safety instructions provided in this guide.

General Safety Guidelines

- Ensure that the product is used only for its intended purpose.
- Regularly inspect the rings for any signs of wear or damage before each use.
- If you notice any defects or issues, discontinue use immediately and consult a qualified technician.
- Keep the product out of reach of children and vulnerable individuals.
- Always follow the manufacturer's guidelines for installation and usage to avoid accidents.
- In case of an accident or injury, report it to the relevant authorities.

Specific Safety Precautions for Use

- **Recoil Control:** Ensure that the recoil control key is properly engaged to prevent shifting or movement of the rings during use.
- **Optics Removal:** When detaching the optics, do so gently to avoid damaging the scope or the rings.
- **Tightening Screws:** Use the appropriate Torx tool to tighten the screws securely, but avoid overtightening which may damage the rings.
- **Compatibility Check:** Ensure that the rings are compatible with your scope and mounting base to prevent accidents.
- **Environmental Conditions:** Avoid using the rings in extreme weather conditions that may affect their performance.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools, including a Torx T15 socket cap screw tool.
- Ensure the mounting base is clean and free from debris.

2. Installation:

- Position the Maxima QD rings on the mounting base.
- Align the rings with the desired location for your optics.
- Insert and handtighten the Torx screws into the rings. Ensure they are seated properly.
- Use the Torx tool to tighten the screws securely, but do not overtighten.

3. Optics Attachment:

- Carefully place your scope in the rings.
- Adjust the position of the optics as needed for eye relief and comfort.
- Tighten the lever on the rings to secure the optics in place.

4. Removing and Reattaching Optics:

- To remove, pull out on the lever and turn it to the desired position.

- Let the lever snap back into place.
- To reattach, align the optics and repeat the tightening process.

5. Final Checks:

- After installation, check the alignment and ensure that the optics are secure.
- Test the functionality of the quick detach feature before heading out to use your equipment.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- Consider recycling options where available to minimize environmental impact.

Contact Information for Further Support

For any inquiries regarding safety or product issues, please refer to the contact information provided with your product packaging or visit the manufacturer's website for more details.

By following these safety instructions, you can ensure a safe and effective experience with your Maxima Quick Detach Rings. Thank you for your attention to these important guidelines.

Säkerhetsinstruktioner för MAXIMA QUICK DETACH RINGS

Introduktion

Tack för att du valt MAXIMA QUICK DETACH RINGS från Warne Mfg. Company. Dessa ringsystem är designade för att ge en säker och pålitlig montering av kikarsikten. För att säkerställa säker användning och långvarig prestanda, vänligen följ dessa säkerhetsinstruktioner noggrant.

Allmänna säkerhetsriktlinjer

- Se till att produkten är avsedd för ditt specifika kikarsikte och gevär.
- Använd endast produkten enligt tillverkarens anvisningar.
- Kontrollera regelbundet att alla delar är i gott skick och att inga skador har uppstått.
- Förvara produkten på en säker plats, utom räckhåll för barn och husdjur.
- Rapportera eventuella skador eller defekter till återförsäljaren.

Specifika säkerhetsåtgärder för användning

- Använd alltid rätt verktyg för installation och justering av ringsystemet.
- Kontrollera att ringarna är korrekt fästa innan du använder ditt kikarsikte.
- Var försiktig med skarpa kanter och verktyg under installationen.
- Använd inte produkten om du misstänker att den har skadats.
- Undvik att utsätta ringarna för extrema temperaturer eller fukt.

Instruktioner för installation och användning

1. Förberedelse

- Läs igenom hela manualen innan installation.
- Kontrollera att du har alla nödvändiga verktyg (Torxstil T15 skruvmejsel).

2. Installation

- Placera ringarna på Warnebasen eller kompatibla Weaverkorsspår.
- Använd Torxstil T15 skruvarna för att fästa ringarna. Dra åt skruvarna jämnt för att undvika snedvridning.
- Se till att spännet är korrekt indexerat innan det snäpps på plats.

3. Användning

- Kontrollera att kikarsiktet sitter ordentligt innan varje användning.
- Om du tar bort kikarsiktet, se till att återmontera det enligt anvisningarna för att behålla nollpunkten.

4. Underhåll

- Rengör ringarna regelbundet med en mjuk trasa för att avlägsna smuts och skräp.
- Inspektera ringarna och baserna för tecken på slitage eller skador.

Avfallshanteringsanvisningar

- Kasta inte produkten i hushållsavfallet.

- Återvinn delar av produkten enligt lokala riktlinjer för metall och plast.
- Konsultera din lokala avfallshanteringsmyndighet för korrekt kassering av produkter.

Kontaktinformation för ytterligare support

För frågor eller support, vänligen kontakta din återförsäljare eller besök tillverkarens webbplats för mer information.

Návod k použití a bezpečnostní pokyny pro MAXIMA QUICK DETACH RINGS

Úvod

Děkujeme, že jste si zakoupili Maxima Quick Detach Rings od společnosti Warne MFG. Company. Tento produkt byl navržen tak, aby poskytoval bezpečné a efektivní upevnění optiky na vaší pušce. Prosím, pečlivě si přečtěte tento návod a dodržujte všechny bezpečnostní pokyny, abyste zajistili bezpečné a správné používání produktu.

Obecné bezpečnostní pokyny

- Před použitím produktu si důkladně přečtěte všechny pokyny.
- Zkontrolujte, zda jsou všechny komponenty produktu v dobrém stavu a bez poškození.
- Používejte výrobek pouze pro zamýšlený účel a v souladu s pokyny výrobce.
- Udržujte výrobek mimo dosah dětí a zranitelných osob.
- V případě jakýchkoli nejasností nebo pochybností se obraťte na odborníka.

Specifické bezpečnostní opatření pro použití

- Před instalací se ujistěte, že je puška bezpečně zajištěna a není nabitá.
- Při montáži kroužků Maxima QD dbejte na správné umístění a utažení.
- Nikdy nepoužívejte poškozené nebo opotřebované komponenty.
- Při demontáži optiky postupujte opatrně, abyste se vyhnuli poškození kroužků nebo pušky.
- Při používání kroužků na puškohledech dodržujte doporučené hodnoty pro kontrolu zpětného rázu.

Pokyny pro instalaci a použití

1. Příprava:

- Zkontrolujte, zda máte všechny potřebné nástroje, včetně Torx T15 šroubováku.
- Ujistěte se, že puška je bezpečně zajištěna a není nabitá.

2. Instalace kroužků:

- Umístěte kroužky na základny puškohledu.
- Otočte páčku kroužku do požadované polohy.
- Upevněte kroužky pomocí Torx T15 šroubů. Ujistěte se, že jsou šrouby utaženy podle doporučení výrobce.

3. Použití:

- Před každým použitím se ujistěte, že jsou kroužky správně upevněny.
- Při odstraňování optiky z pušky použijte indexovatelný systém páčky pro snadnou demontáž.
- Po opětovném připevnění optiky zkontrolujte, zda je nastavení nuly zachováno.

Pokyny pro likvidaci

- Při likvidaci produktu se řiďte místními předpisy o odpadech.
- Pokud je výrobek poškozen nebo nefunkční, zlikvidujte ho odpovědně, aby nedošlo k ohrožení životního prostředí.

Kontaktní informace pro další podporu

V případě dotazů nebo potřebné podpory se obraťte na autorizovaný servis nebo prodejce. Ujistěte se, že máte k dispozici informace o produktu, včetně modelu a sériového čísla.

Tento návod byl vypracován v souladu s požadavky na bezpečnost produktů podle EU General Product Safety Regulation (GPSR). Dodržováním uvedených pokynů zajistíte bezpečné používání produktu a minimalizujete rizika.